

Pressure sensor liquids

Active sensor (4...20 mA) for measuring the pressure in liquid mediums for air conditioning, heating and water applications. Suitable for plants with refrigerant. NEMA 4 / IP65 rated enclosure.





| | _ | |
|------|--------|--------|
| IVna | ()\/c | |
| IYPE | Ove | erview |

| Туре | Measuring Range Pressure | Output Signal Active Pressure | Overpressure Limit | Burst Pressure |
|----------|-----------------------------|----------------------------------|--------------------|----------------|
| 22WP-134 | 04 bar | 420 mA | 8 bar | 12 bar |
| 22WP-135 | 06 bar | 420 mA | 12 bar | 18 bar |
| 22WP-136 | 010 bar | 420 mA | 20 bar | 30 bar |
| 22WP-137 | 016 bar | 420 mA | 32 bar | 48 bar |

| Technical Data | | | |
|-----------------|-------------------------------------|---|--|
| Electrical data | Power Supply DC | 1524 V, ±10%, 0.5 W | |
| | Electrical connection | Plug for wire 0.51.5 mm² | |
| | Cable entry | MVS plug according to DIN EN175301-803 / Type A | |
| Functional data | Sensor Technology | Strain gauge on precious metal | |
| | Mechanical connection | pressure connector: G1/4" | |
| | Media | Water | |
| Measuring data | Measured values | Relative pressure | |
| | Accuracy pressure | ±0.5% FS @ 25 °C | |
| | Total errors for final temperatures | at maximum temperatures -40 °C: <= 2% FS 105 °C: <= 2% FS | |
| Materials | Housing seal | FKM fluororubber, Silicone-free | |
| | Housing | Stainless steel 1.4301 | |
| Safety data | Ambient temperature | -40105 °C [-40220 °F] | |
| | Medium temperature | -40125 °C [-40255 °F] | |
| | Protection class IEC/EN | III Protective extra-low voltage (PELV) | |
| | Protection class UL | UL Class 2 Supply | |
| | EU Conformity | CE Marking | |
| | Degree of protection IEC/EN | IP65 | |
| | Degree of protection NEMA/UL | NEMA 4 | |
| | Quality Standard | ISO 9001 | |
| | Weight | 0.12 lbs | |
| | | - | |



Safety notes



The installation and assembly of electrical equipment should only be performed by authorized personnel.

This device has been designed for use in stationary heating, ventilation and air conditioning systems and must not be used outside the specified field of application. Unauthorised modifications are prohibited. The product must not be used in relation with any equipment that in case of a failure may threaten human, animals or assets.

Ensure all power is disconnected before installing. Do not connect to live/operating equipment.


Please comply with

- · Local laws, health & safety regulations, technical standards and regulations
- Condition of the device at the time of installation, to ensure safe installation
- This data sheet and installation manual

Accessories

| Optional Accessories | Description | Туре |
|----------------------|--|------------|
| | Adapter G 1/4" (internal thread) to G 1/2" (external thread) | A-22WP-A02 |

Wiring diagram



Dimensions

